

Usability Heuristics for Eye-controlled User Interfaces

Korok Sengupta

University of Koblenz, Germany

Chandan Kumar

University of Koblenz, Germany

Steffen Staab

University of Koblenz, Germany

University of Southampton, UK

Evolution of affordable assistive technologies like eye tracking help people with motor disabilities to access information on the Internet or work on computers. However, eye tracking environments need to be specially built for better usability and accessibility of the content and should not be on interface layouts that are conducive to conventional mouse or touch based interfaces. In this work, we argue the need of the domain specific heuristic checklist for eye-controlled interfaces, which conforms to the usability, design principles and less demanding from cognitive load perspective. It focuses on the need to understand the product in use inside the gaze based environment and then apply the heuristic guidelines to design them. We propose an eight-point questionnaire to validate the usability heuristic guidelines for eye-controlled interfaces.

Keywords: heuristic, usability, cognitive load, eye tracking, eye movement, user interfaces

Introduction

Due to the evolution of low cost eye trackers and its growing impact as assistive technology, several eye-controlled softwares are available that assist people to interact with the application interfaces by eye gaze commands¹ (Porta & Ravelli, 2009; C. Kumar, Menges, Müller, & Staab, 2017). More specifically, eye tracking environment enables people with motor disabilities to communicate with computer applications which is usually limited to only conventional interaction tools like the mouse, keyboard or touch based interfaces.

The design of user interfaces depends highly on the device that is selected as primary input, i.e., the look and feel of interface elements are acclimatized to mouse and keyboard interaction in conventional interfaces. However, when a different physical input device like eye tracker is the primary source, the interface elements needs to be adapted to be more appropriate for that device. In that regard, eye gaze as input is a challenging phenomena due to the limitation of eye trackers like visual angle, calibration errors, drift, and inherent eye jitter. Furthermore, “Midas Touch” is another major problem with eye-controlled interaction since it is difficult to discrimi-

nate between inspections and selections (Jacob & Stellmach, 2016). There have been several approaches which deals with these issues by means of gaze signal smoothing, enlarged and customized elements, unambiguous navigation, visual feedback etc. (C. Kumar, Menges, & Staab, 2016; M. Kumar, Winograd, Paepcke, & Klingner, 2007; Majoranta, MacKenzie, Aula, & Riihä, 2006). These approaches do provide relevant methods and discussions for gaze-enhanced design. However the field is continuously evolving and it would be consequential to determine the criterion for relevant assessment of eye-controlled interfaces. Hence, in this position paper we argue the need to establish pertinent usability heuristics for gaze-based user interfaces.

Jakob Nielsen, in his guidelines, laid out ten usability heuristics for interface design (Nielsen & Molich, 1990). This has been widely accepted and adopted to not just web interfaces but also for different environments (Mankoff et al., 2003; Sutcliffe & Gault, 2004; Mi, Cavuoto, Benson, Smith-Jackson, & Nussbaum, 2014; Röcker & Haar, 2006). While Nielsen’s work (Nielsen, 1994) forms the backbone of many domain specific heuristic guidelines, it is also important for us to understand stress indicators that come from user interfaces. Prolonged gaze to operate eye-controlled user interfaces lead to fatigue and subsequently wrong selection and high cognitive load. Lupin et al. (Lupien, Maheu, Tu, Fiocco, & Schramek, 2007) stated that increase in cognitive load also happens when experiencing *unpredictability*, *un-*

The 2017 COGAIN Symposium: Communication by Gaze Interaction
Wuppertal, Germany. August 19th and 21st, 2017
This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/> or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.

¹<http://www.mygaze.com/products/mygaze-assistive>

certainty and unfamiliarity from the user interfaces (Lupien et al., 2007), thereby evoking a *sense of loss or not having control* (Henry & Grim, 1990) of the navigation that leads to *perception of loss of self-esteem* (Dickerson & Kemeny, 2004).

Moraveji et al. (Moraveji & Soesanto, 2012) focused on the psychophysiology of stress and came out with some points of measure to understand and control them - ability to control interruption, reduction in feeling overwhelmed, use of appropriate tone and emotion, positive feedback to user inputs, acknowledge user actions and demystify user interface.

Usability Heuristics for Eye-controlled UI

Following the guidelines mentioned by Rusu et al. (Rusu, Roncagliolo, Rusu, & Collazos, 2011) for developing new usability heuristic and closely adhering to Kumar et al. (M. Kumar et al., 2007), Chitty (Chitty, 2013), Hatfield et al. (Hatfield, Jenkins, Jennings, & Calhoun, 1996), a ten-point guideline is described which could provide direction to design and evaluation of eye-controlled user interfaces.

Design And Aesthetics:

#1: Visibility of main interaction elements - for easy accessibility and coherence in eye-controlled interfaces, thus reducing the feeling of uncertainty of accessing the interface to navigate across content.

#2: Aesthetic design - for comfortable viewing and navigation thus reducing eye strain and cognitive load.

#3: Consistency of design - to ensure that all icons, typefaces and navigational points are consistent thus leading to lesser confusion and better usability.

#4: Feedback - to ensure better usability and less error.

Navigation:

#5: Direct User-Controls - provides the user with the ability to control input against inspection. This reduces wrong activation leading to less cognitive load and feeling of being overwhelmed.

#6: Optimized work-flow ensuring lesser error - leads to quicker task completion. In eye-controlled user interfaces, the lesser the multi-level menus, the better and more precise is the user experience.

Error and Help:

#7: Optimum Activation time - leads to lesser activation of wrong keys due to extremely low dwell times thus minimizing the "Midas Touch" problem, and reducing the sense of frustration and fatigue.

#8: Intelligent Design for Error handling and Recovery - to handle error in a positive fashion by reducing the feeling of being overwhelmed and by helping recover from the error to the last correct state.

#9: Gaze Accuracy - to ensure that there is no drift in sig-

nal which may lead to activation of wrong keys thus creating confusion and a sense of being overwhelmed.

#10: Graphical Help and Documentation - leads to quicker understanding of the environment and faster diagnosis than error handling in complete text based documentation.

Subjective assessment of the interfaces is a significant aspect of development cycle, i.e., to validate user satisfaction and substantiate the application. Different application environments often employ System Usability Scale (SUS) (Lewis & Sauro, 2009) or compiles customized questionnaires for this purpose. In the following we describe a questionnaire that closely matches the discussed guidelines for eye-controlled interfaces, along with the SUS measurements, which can help us to assess the aspects of the gaze-based interfaces that can be improved for end-users.

I) How comfortable was the size and the position of main interaction elements? (#1 of guidelines)

II) How effective was the feedback from interaction element? (#4 of guidelines)

III) How aesthetic and consistent was the design and the interaction elements? (#2, #3 of guidelines)

IV) How easy was it to navigate from one point to another? (#6 of guidelines)

V) How easy was it to interact with the interface? (#5 of guidelines)

VI) How comfortable was the selection time of interaction elements? (#7 of guidelines)

VII) How efficient was it to handle and recover errors from it? (#8 of guidelines)

VIII) How correctly was the system reacting to your gaze position? (#9 of the guidelines)

IX) How easy was it to access help if required? (#10 of the guidelines)

Heuristic evaluation based on usability heuristics is quite a prominent method of usability inspection. But generalizing heuristics could lead to missing of domain specific problems. In this paper we discuss some guidelines and an evaluation questionnaire that concerns the design and implementation of eye-controlled user interfaces. The guidelines discussed here follow the balance of generality and specificity. Further development, and evaluation of these guidelines against the conventional guidelines (Nielsen, 2003), for various eye-controlled user interfaces (C. Kumar et al., 2016; Menges, Kumar, Müller, & Sengupta, 2017) is in line for the future work.

Acknowledgement

This work is part of project MAMEM² that has received funding from the European Union's Horizon 2020 research & innovation program under grant agreement number: 644780.

²<http://www.mamem.eu>

References

- Chitty, N. (2013). User fatigue and eye controlled technology. *OCAD University*.
- Dickerson, S. S., & Kemeny, M. E. (2004). Acute stressors and cortisol responses: a theoretical integration and synthesis of laboratory research. *Psychological bulletin*, 130(3), 355.
- Hatfield, F., Jenkins, E. A., Jennings, M. W., & Calhoun, G. (1996). Principles and guidelines for the design of eye/voice interaction dialogs. In *Human interaction with complex systems, 1996. hics'96. proceedings., third annual symposium on* (pp. 10–19).
- Henry, J. P., & Grim, C. E. (1990). Psychosocial mechanisms of primary hypertension. *Journal of hypertension*, 8(9), 783–793.
- Jacob, R., & Stellmach, S. (2016, August). What you look at is what you get: Gaze-based user interfaces. *interactions*, 23(5), 62–65. Retrieved from <http://doi.acm.org/10.1145/2978577>
- Kumar, C., Menges, R., Müller, D., & Staab, S. (2017). Chromium based framework to include gaze interaction in web browser. In *Proceedings of the 26th international conference on world wide web companion* (pp. 219–223). Republic and Canton of Geneva, Switzerland: International World Wide Web Conferences Steering Committee. Retrieved from <https://doi.org/10.1145/3041021.3054730>
- Kumar, C., Menges, R., & Staab, S. (2016). Eye-controlled interfaces for multimedia interaction. *IEEE MultiMedia*, 23(4), 6–13.
- Kumar, M., Winograd, T., Paepcke, A., & Klingner, J. (2007). *Gaze-enhanced user interface design* (Tech. Rep.). Stanford InfoLab.
- Lewis, J., & Sauro, J. (2009). The factor structure of the system usability scale. *Human centered design*, 94–103.
- Lupien, S. J., Maheu, F., Tu, M., Fiocco, A., & Schramek, T. E. (2007). The effects of stress and stress hormones on human cognition: Implications for the field of brain and cognition. *Brain and cognition*, 65(3), 209–237.
- Majaranta, P., MacKenzie, I. S., Aula, A., & Riih a, K.-J. (2006). Effects of feedback and dwell time on eye typing speed and accuracy. *Universal Access in the Information Society*, 5(2), 199–208.
- Mankoff, J., Dey, A. K., Hsieh, G., Kientz, J., Lederer, S., & Ames, M. (2003). Heuristic evaluation of ambient displays. In *Proceedings of the sigchi conference on human factors in computing systems* (pp. 169–176).
- Menges, R., Kumar, C., M uller, D., & Sengupta, K. (2017). Gazetheweb: A gaze-controlled web browser. In *Proceedings of the 14th web for all conference*. ACM. Retrieved from <http://dx.doi.org/10.1145/3058555.3058582>
- Mi, N., Cavuoto, L. A., Benson, K., Smith-Jackson, T., & Nussbaum, M. A. (2014). A heuristic checklist for an accessible smartphone interface design. *Universal access in the information society*, 13(4), 351–365.
- Moraveji, N., & Soesanto, C. (2012). Towards stress-less user interfaces: 10 design heuristics based on the psychophysiology of stress. In *Chi'12 extended abstracts on human factors in computing systems* (pp. 1643–1648).
- Nielsen, J. (1994). Usability inspection methods. In *Conference companion on human factors in computing systems* (pp. 413–414).
- Nielsen, J. (2003). *Usability 101: Introduction to usability*.
- Nielsen, J., & Molich, R. (1990). Heuristic evaluation of user interfaces. In *Proceedings of the sigchi conference on human factors in computing systems* (pp. 249–256).
- Porta, M., & Ravelli, A. (2009). Weyeb, an eye-controlled web browser for hands-free navigation. In *Human system interactions, 2009. hsi'09. 2nd conference on* (pp. 210–215).
- R ocker, C., & Haar, M. (2006). Exploring the usability of videogame heuristics for pervasive game development in smart home environments. In *Proceedings of the third international workshop on pervasive gaming applications—pergames* (pp. 199–206).
- Rusu, C., Roncagliolo, S., Rusu, V., & Collazos, C. (2011). A methodology to establish usability heuristics. In *Proc. 4th international conferences on advances in computer-human interactions (achi 2011), iaria* (pp. 59–62).
- Sutcliffe, A., & Gault, B. (2004). Heuristic evaluation of virtual reality applications. *Interacting with computers*, 16(4), 831–849.